

FLOOR CARE GUIDE FOR HARO TRITTY LAMINATE FLOORS

HARO[®]
TRITTY



MAINTAINING HARO TRITTY LAMINATE FLOOR – IT'S AS SIMPLE AS THIS

You have chosen a HARO TRITTY Laminate Floor. HARO TRITTY Laminate Floors are distinguished by an especially high wear and impact resistance and are largely scratch and dent resistant. They are also resistant to cigarette burn marks and fading under UV light.

The high-grade surface layer and the special aquaTec edge impregnation make TRITTY exceptionally hard-wearing. Dust and dirt cannot settle permanently and can easily be vacuumed or wiped away.

This ensures a pleasant atmosphere which is very much appreciated, especially by allergy sufferers.

HARO TRITTY 100 strip beech beige (wood reproduction)





(1)



(2)



(3)



(4)

AFTER INSTALLATION

Immediately after laying HARO TRITTY you should carry out first treatment with HARO Secura-A.

HARO Secura-A significantly reduces the absorption of water during damp mopping and protects the seams and surface against moisture, thus preventing a swelling of the board edges.

And here's how it's done:

Remove all dust, dirt and grit from the flooring surface (do not damp mop!). The floor must be completely dry before treatment (1).

Apply HARO Secura-A evenly and as thin as possible using a double-blade spatula. Treat the floor in sections of about 3 sq.m. (30 sq.ft) (2). Immediately buff each section after application using a HARO Polishing Cloth (3) or a suitable floor care machine (4) (wrap a HARO Polishing Cloth around the pad!). Never let HARO Secura A set-up or dry without buffing. Do not walk on buffed areas.

Repeat the above procedure one section at a time to finish the entire flooring surface. It is essential to buff HARO Secura-A until the flooring surface is clear without streaks.


Do not walk on the finished floor for about 8 hours.

Drench used cloths in water or hang up outdoors. Do not fold or crumple up used cloths. Dispose of in a safe way in accordance with local regulations.

Apart from first treatment immediately after laying, we recommend carrying out intensive care with HARO Secura-A once a year, as described above.



HARO TRITTY 100 plank 1-strip beech (wood reproduction)



HARO CORKETT, Design Co

DRY CLEANING

It is usually absolutely sufficient to clean HARO TRITTY dry using a mop, soft broom or vacuum cleaner. You can damp mop the floor whenever required. For especially effective dry cleaning we recommend HARO Easy Clean, the cleaning cloth for water-free cleaning.

DAMP CLEANING

We recommend damp mopping your HARO TRITTY floor regularly with HARO Laminate Floor Cleaner. The frequency hereby depends on the wear and tear your floor is subjected to. HARO Laminate Floor Cleaner is a solvent-free cleaner without greasing or film-building substances. It effectively removes oily and greasy stains.

And here's how it's done:

Add about 200 ml (7 fl.oz.) of HARO Laminate Floor Cleaner to 8–10 litres (2-2.5 gal) of water. Apply the solution evenly to the flooring surface with a well-wrung cloth. Do not make the floor too wet and **never leave puddles.**

By buffing the treated surface dry with a HARO Polishing Cloth you can further enhance the gloss of your floor.



HARO TRITTY 75 strip maple (wood reproduction)



STAIN REMOVAL

You can remove difficult spots and stains (tar stains, colour crayon, etc.) very easily by spot-treating them with HARO Stain Remover. Wipe off the spot or stain first using a dry HARO Polishing Cloth. Spray HARO Stain Remover on the area to be treated and leave for a few minutes. Clean and buff dry with a HARO Polishing Cloth. That's it.

INTENSIVE CARE

To ensure a long lifetime of your floor, we recommend – apart from first treatment immediately after laying – to carry out intensive care with HARO Secura-A once a year (as described in the chapter “After installation”).




HARO TRITTY 75 strip beech beige (wood reproduction)



(1)



(2)



(3)

USEFUL TIPS

1. Climatic conditions

What is good for people is also good for your HARO floor. A room temperature of 20°C (68°F) at a relative humidity of about 50%–60% is ideal. During the heating season, this relative humidity value is often fallen below to a considerable extent. To prevent the wood from drying out, it is advisable to use an electrical humidifier (1) (available in HARO Shop), right from the beginning of the heating season.

2. Additional protection for your floor

To preserve the quality and beauty of your floor we recommend using protective pads under chairs and furniture legs (2) (available in HARO Shop). Place quality walk-off mats at entrances, garages and basements to minimise tracked-in dirt, grit and moisture. For additional protection, it is a good idea to place polycarbonate protective mats (3) from HARO Shop under castor-fitted chairs.

MAINTAINING HARO TRITTY LAMINATE FLOOR

	HARO Easy Clean	HARO Secura-A	HARO Laminate Floor Cleaner	HARO Stain Remover	HARO Polishing Cloth	HARO Double-Blade Spatula
						
After installation	–	x	–	–	x	x
Cleaning	Dry cleaning	x	–	–	–	–
	Damp cleaning	–	–	x	x	–
Stain removal	–	–	–	x	x	–
Intensive care	–	x	–	–	x	x

If you have any further questions or suggestions, your HARO dealer is always available.

HARO[®]
QUALITY FLOORING

Hamberger Industriewerke GmbH

P.O.B. 10 03 53 · 83003 Rosenheim · Germany

Telephone +49 (8031) 700-0 · Telefax +49 (8031) 700-600/610

E-mail mail@hamberger.de · Internet www.haro.com